SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Octopus Fluids Resin Ink MILK

Further trade names

RI-WH010-030

UFI: 6M2T-DY1V-QQQ9-Q7EJ

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

creative ink

1.3. Details of the supplier of the safety data sheet

Company name:	Octopus Fluids GmbH & Co.KG	
Street:	Hamburger Str. 14	
Place:	D-01067 Dresden	
Telephone:	+ 49 351 7968925	Telefax: +49 351 8894982
e-mail:	mail@octopus-fluids.de	
Contact person:	Lange	
e-mail:	mail@octopus-fluids.de	
Internet:	www.octopus-fluids.de	

1.4. Emergency telephone number:

+ 49 351 7968925 (9 a.m. to 4 p.m.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 2; H225
Eye Irrit. 2; H319
STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

propan-2-ol; isopropyl alcohol; isopropanol
1-methoxy-2-propanol; monopropylene glycol methyl ether

Signal word: Danger

Pictograms:

Hazard statements

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P403+P235	Store in a well-ventilated place. Keep cool.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:

Hazard statements

H336

Precautionary statements

P101-P102-P261-P271

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			40 - < 50 %
	200-661-7	603-117-00-0		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
1569-01-3	1-Propoxy-2-propanol			5 - < 10 %
	216-372-4		01-2119474443-37	
	Flam. Liq. 3, Eye Irrit. 2; H226 H319			
107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether			5 - < 10 %
	203-539-1	603-064-00-3		
	Flam. Liq. 3, STOT SE 3; H226 H336			
64-17-5	ethanol; ethyl alcohol			5 - < 10 %
	200-578-6	603-002-00-5		
	Flam. Liq. 2, Eye Irrit. 2; H225 H319			
77-99-6	Propylidintrimethanol			0.1 - < 0.3 %
	201-074-9		01-2119486799-10	
	Repr. 2; H361fd			
78-93-3	butanone; ethyl methyl ketone			< 0.1 %
	201-159-0	606-002-00-3		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
107-98-2	203-539-1	1-methoxy-2-propanol; monopropylene glycol methyl ether	5 - < 10 %
	dermal: LD50 = 11000 mg/kg; oral: LD50 = > 5000 mg/kg		

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Provide fresh air. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After contact with skin

Wash with plenty of water. Take off contaminated clothing and wash it before reuse.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Rinse mouth immediately and drink 1 glass of of water.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water spray jet, Carbon dioxide (CO2), Foam, Extinguishing powder.

5.2. Special hazards arising from the substance or mixture

Highly flammable. Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Explosion risk.

6.3. Methods and material for containment and cleaning up

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances.

7.3. Specific end use(s)

creative ink

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

CAS No	Name of agent	ppm	mg/m³	fib/cm³	Category	Origin
107-98-2	1-Methoxypropan-2-ol	100	375		TWA (8 h)	
		150	568		STEL (15 min)	
78-93-3	Butanone	200	600		TWA (8 h)	
		300	900		STEL (15 min)	

8.2. Exposure controls

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Use of protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Thermal hazards

Flame-retardant protective clothing. Wear anti-static footwear and clothing

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	white
Odour:	Alcohol

Changes in the physical state

Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	82 °C
Flash point:	12 °C

Flammability

Solid/liquid:	not applicable
Gas:	not applicable

Explosive properties

The product is not: Explosive.

Lower explosion limits:	not determined
Upper explosion limits:	not determined
Auto-ignition temperature:	not determined
Decomposition temperature:	not determined
pH-Value:	not determined
Water solubility:	not determined

Solubility in other solvents

not determined

Partition coefficient n-octanol/water:	not determined
Vapour pressure:	not determined
Density:	1,032 g/cm³
Relative vapour density:	not determined

9.2. Other information

Information with regard to physical hazard classes

Oxidizing properties

The product is not: oxidising.

Other safety characteristics

Solid content:	not determined

Evaporation rate: not determined

Further Information

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether				
	oral	LD50 > 5000 mg/kg	Rat	IUCLID	
	dermal	LD50 11000 mg/kg	Rabbit		

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (propan-2-ol; isopropyl alcohol; isopropanol)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

No information available.

Further information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

The product is not: Ecotoxic.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] | [d]	Species	Source	Method
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol					
	Acute algae toxicity	ErC50 > 100 mg/l	72 h			
107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether					
	Acute fish toxicity	LC50 4600 - 10000 mg/l	96 h	Leuciscus idus	IUCLID	
	Acute algae toxicity	ErC50 > 1000 mg/l	72 h	Selenastrum capricornutum		
	Acute crustacea toxicity	EC50 > 500 mg/l	48 h	Daphnia magna	IUCLID	

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether	-0,437

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.
The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.
No information available.

12.7. Other adverse effects

No information available.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	UN 1263
14.2. UN proper shipping name:	PAINT
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3

Classification code:	F1
Special Provisions:	163 367 640D 650
Limited quantity:	5 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	33
Tunnel restriction code:	D/E

Marine transport (IMDG)

14.1. UN number or ID number:	UN 1263
14.2. UN proper shipping name:	FARBE
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3

Special Provisions:	163, 367
Limited quantity:	5 L
Excepted quantity:	E2
EmS:	F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	UN 1263
14.2. UN proper shipping name:	FARBE
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3

Special Provisions:	A3 A72 A192
Limited quantity Passenger:	1 L
Passenger LQ:	Y341
Excepted quantity:	E2
IATA-packing instructions - Passenger:	353
IATA-max. quantity - Passenger:	5 L
IATA-packing instructions - Cargo:	364
IATA-max. quantity - Cargo:	60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Combustible liquid.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

2010/75/EU (VOC):	65,86 % (679,67 g/l)
2004/42/EC (VOC):	65,86 % (679,67 g/l)
Information according to 2012/18/EU (SEVESO III):	P5c FLAMMABLE LIQUIDS

National regulatory information

Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).
Water hazard class (D):	1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

CLP: Classification, labelling and Packaging
REACH: Registration, Evaluation and Authorization of Chemicals
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
UN: United Nations
CAS: Chemical Abstracts Service
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration
ATE: Acute toxicity estimate
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%
LL50: Lethal loading, 50%
EL50: Effect loading, 50%
EC50: Effective Concentration 50%
ErC50: Effective Concentration 50%, growth rate
NOEC: No Observed Effect Concentration
BCF: Bio-concentration factor
PBT: persistent, bioaccumulative, toxic
vPvB: very persistent, very bioaccumulative
ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
RID: Regulations concerning the international carriage of dangerous goods by rail
MARPOL: International Convention for the Prevention of Marine Pollution from Ships
IBC: Intermediate Bulk Container
VOC: Volatile Organic Compounds
SVHC: Substance of Very High Concern
For abbreviations and acronyms, see table at http://abbrev.esdscom.eu

Classification for mixtures and used evaluation method according to regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H336	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)